

TL-A2022 22T

FEATURES

- Welded base and cylinders to assure strength and eliminated leaks
- Chromed pump piston and ram for added rust resistance
- Extension screw gives added height when necessary
 - All air power device for easy operation
 - Super low minimum height for easy access
- Meets ANS/ASME PALD & CE/GS standards



SPECIFICATIONS

Model	Weight Capacity (Ton)	Min Saddle Height (mm)	Max Saddle Height (mm)	Air Pressure (Mpa)	Net Weight (Kg)
TL-A2022	22	210(8.3")	525(20.7")	0.7-1.0	46(10Lbs)

DIMENSIONS

Model	A mm(in.)	B mm(in.)	C mm(in.)	D mm(in.)	E mm(in.)	F mm(in.)	G mm(in.)	Handle Length mm(in.)
TL-A2022	245(9.6)	322(12.7)	570(22.4)	205(8.1)	210(8.3)	525(20.7)	1210(47.6)	1046(41.1)

TL-A2122 22T

FEATURES

- Welded base and cylinders to assure strength and eliminated leaks
 - Chromed pump piston and ram for added rust resistance
 - Extension screw gives added height when necessary
 - All air power device for easy operation
 - Super low minimum height for easy access
 - Meets ANS/ASME PALD & CE/GS standards



SPECIFICATIONS

Model	Weight Capacity (Ton)	Min Saddle Height (mm)	Max Saddle Height (mm)	Air Pressure (Mpa)	Net Weight (Kg)
TL-A2122	22	185(7.3")	465(18.3")	0.7-1.0	42(93Lbs)

DIMENSIONS

Model	A mm(in.)	B mm(in.)	C mm(in.)	D mm(in.)	E mm(in.)	F mm(in.)	G mm(in.)	Handle Length mm(in.)
TL-A2122	245(9.6)	322(12.7)	570(22.4)	205(8.1)	185(7.3)	465(18.3)	1210(47.6)	1046(41.1)

TL-5404 4T

FEATURES

- Electrically welded base and cylinder to assure strength and eliminated leaks
- Chromed pump piston and ram for added rust resistance
- Two-position lift pad permits handling of lift truck configurations with flat or edged surfaces.
- Meets ANSI/ASME PALD & CE/GS standards.



SPECIFICATIONS

Model	Capacity (Ton)	Low Height (mm)	High Height (mm)	Net Weight Kg
TL-5404	4	65	406(18.1")	33(72.8Lbs)