

Air Jacks



Select the jack pad to lift higher



Advanced switch, very easy to operate



High performance air spring, the working degree is over 100,000 times



TL-3622
TL-3632



TL-3623
TL-3633



TL-3622L
TL-3632L



TL-3623L
TL-3633L



SPECIFICATIONS



Model	Capacity	Min Height (mm)	Max Height (mm)	Lifting Time	Working Temp	N. W/G.W (kg)	Package Size (mm)	QTY/20'CY (PCS)
TL-3622	2Ton	100	295	3 sec	-60°C-50°C	14/14.5	485x330x195	800
TL-3623	2Ton	100	295	3 sec	-60°C-50°C	16/17	485x330x195	500
TL-3622L	2Ton	125	400	4 sec	-60°C-50°C	17/17.5	485x330x195	800
TL-3623L	2Ton	125	400	4 sec	-60°C-50°C	19/20	485x330x195	500
TL-3632	3Ton	100	295	4 sec	-60°C-50°C	23/25	485x330x195	600
TL-3633	3Ton	100	295	4 sec	-60°C-50°C	25/27	485x330x195	600
TL-3632L	3Ton	145	420	5 sec	-60°C-50°C	27/29	485x330x195	600
TL-3633L	3Ton	145	420	5 sec	-60°C-50°C	29/31	485x330x195	600