
EVA 373 AS





Antistatic suction hose; EVA <10¹¹ Ω , light, crush resistant, lightweight

Applications

• for domestic and industrial vacuum cleaners

Properties

- surface resistance $<10^{11} \, \Omega$
- · crush resistant
- light model
- highly flexible
- good resistance to alkalis and acids
- good resistance to UV and ozone

- · gas and liquid tight
- floatable
- light weight
- conform to RoHS guideline

Temperature Range

• -25°C to 65°C

Design, Material

- 1. self-supporting profile design
- 2. open profile geometry; wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)
- as a pre-assembled hose system with CON-NECT connectors
- · customised connectors

| I.D. in / mm | O.D. mm | Under- pressure bar | Bending Radius mm | Weight kg/m | Dimensions in Stock m | Further Production Lengths m | Order No. |
|-----------------|------------|---------------------------|-------------------------|----------------|-----------------------------|---------------------------------------|---------------|
| -/20 | 26,8 | 0,500 | 42,0 | 0,130 | - | 30 | 373-0020-1002 |
| 1 / 25 | 32,2 | 0,500 | 53,5 | 0,150 | 30 | - | 373-0025-1002 |
| -/30 | 38,0 | 0,500 | 62,0 | 0,200 | - | 30 | 373-0030-1002 |
| 1,25 / 32 | 40,4 | 0,500 | 66,0 | 0,240 | 30 | - | 373-0032-1002 |
| 1,36 / 35 | 43,8 | 0,500 | 70,5 | 0,260 | 30 | - | 373-0035-1002 |
| 1,5 / 38 | 47,2 | 0,500 | 74,0 | 0,310 | 30 | - | 373-0038-1002 |
| -/40 | 49,4 | 0,500 | 80,0 | 0,320 | 30 | - | 373-0040-1002 |
| 1,75 / 44-45 | 55,0 | 0,500 | 88,5 | 0,370 | 30 | - | 373-0045-1002 |
| 2 / 50-51 | 60,4 | 0,500 | 97,0 | 0,440 | 30 | - | 373-0050-1002 |
| 2,36 / 60 | 72,0 | 0,500 | 113,0 | 0,670 | 30 | = | 373-0060-1002 |

Accessories





CLAMP 208

CONNECT 227