

CONNECT 226



Soft sleeve for SuperFlex hoses

Properties

- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- easily and quickly fitted
- re-usable (threaded)
- conform to RoHS guideline

Temperature Range

- -20°C to 70°C
- short time to 80°C

Design, Material

wall: high grade soft PVC

Delivery variants

- further diameters available on request.
- black (standard)
- as a pre-assembled hose system with a suitable hose

Suitable for hose

SuperFlex PVC 372

Rec. Adapter Ø mm	Rec. Adapter length mm	Threading depth Hose	Total Length mm	Weight kg/Pcs	Suitable for Hose I.D. mm	Order No.
25	50	45	45	0,050	25	226-0025-0000
32	50	45	45	0,060	32	226-0032-0000
38	50	45	45	0,070	38	226-0038-0000
41	50	45	45	0,070	41	226-0041-0000
44	50	45	45	0,080	44	226-0044-0000
51	50	45	45	0,090	51	226-0051-0000
63	50	45	45	0,130	63	226-0063-0000
70	45	45	45	0,150	70	226-0070-0000
76	45	45	45	0,170	76	226-0076-0000

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 20°C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.