


## 0489 - DOUBLE FEMALE BSPP VALVE WITH THREADED EXHAUST



Allows collection of vented fluids through a threaded vent port.

- full flow
- optimum sealing due to compensating "O" rings
- excellent resistance to scaling due to ball seal configuration

|                                 |   |
|---------------------------------|---|
| <b>maximum working pressure</b> | 40 bar<br>4 MPa<br>580 psi                    |
| <b>working temperature</b>      | -20 to 80 °C<br>-4 to 176 °F<br>253 to 353 °K |
| <b>body</b>                     | NICKEL PLATED BRASS                           |
| <b>retaining nut</b>            | NICKEL PLATED BRASS                           |
| <b>stem</b>                     | BRASS   |
| <b>stem seal</b>                | NBR   |
| <b>'O'-rings</b>                | NBR   |
| <b>ball seal</b>                | NBR   |
| <b>handle</b>                   | ZAMAK   |

| Part No       | C    | C1     | E (mm) | F (mm) | F1 (mm) | H (mm) | H1 (mm) | H2 (mm) | L (mm) | L1 (mm) | M (mm) | ØT (mm) |
|---------------|------|--------|--------|--------|---------|--------|---------|---------|--------|---------|--------|---------|
| LE-0489 07 13 | G1/4 | M5x0,8 | 12     | 24     | 24      | 46     | 43      | 17      | 59     | 31      | 69     | 2       |
| LE-0489 10 17 | G3/8 | M5x0,8 | 12     | 24     | 24      | 46     | 43      | 17      | 59     | 31      | 69     | 2       |
| LE-0489 13 21 | G1/2 | G1/8   | 15     | 27     | 27      | 47     | 44      | 24      | 67     | 34      | 69     | 2       |
| LE-0489 18 27 | G3/4 | G1/4   | 16.5   | 32     | 38      | 63     | 54      | 33      | 80     | 39      | 108    | 2.5     |
| LE-0489 23 34 | G1   | G1/4   | 19     | 41     | 46      | 67     | 57      | 37      | 94     | 47      | 108    | 3       |