

# Trio-Tech™ 3-Way Plastic Valve



Material	PP+GF, (EPDM (O-rings
Temperature Range	(-5) ° (60) °C
Pressure nominal	10.0 bar



Trio-Tech™, Tefen's new 3-Way thermo plastic valves are simple to operate, have reliable performance - efficient valves that can handle tough environmental conditions. Pressure and prolonged operation will not affect Tefen's Trio-Tech™ valves life time. These valves have an open, close or automatic position.

# Trio-Tech™ 3-Way Plastic Valve

## Features & Benefits:

- Heavy duty Trio-Tech™ provides dependable operation and long life; the Trio-Tech™ has only one moveable part, which significantly reduces the grinding and discrepancies.
- High grade construction made of durable PP+FG and chemical resistance EPDM O-ring that provides:
  1. Ability to handle a wide range of aggressive chemicals
  2. Ability to operate in a high pressure such as 10 bar.
- Multiple connectors configurations in two sizes, provides flexibility and operational efficiency, for example:
- Perfect for applications such as filtering systems and hydraulic valves made out of plastic or metal, for example:

Thread Type / Size	¼" BSPT /3*( Hose-barb 8 mm)
	¼" BSPT /3*( 1/8" BSPT-Male )
	¼" BSPT /3*( 1/4" BSPT-Male )
	¼" BSPT / and any combination of: 1/8" BSPT-Male,1/4" BSPT-Male and barb 8 mm

