




# Reducing Bush

## Reducing Bush


### Features:

- High Working Pressure
- Mild Steel - High Grade Material
- Sealing face and threads machined to high tolerance
- High Level Corrosion Resistance Plating (CR3 compliant)
- Bonded Seal Centring Cone
- Available in Stainless Steel 316 or Cupro Nickel



### Benefits:

- Highly resistant to leakage even under severe vibration, pressure pulsation and temperature



BSP 1	BSP 2	Part No	C mm	D mm	E mm	Body A/F mm	Max WP Bar
1/4	1/8	KRRB4-2	29	18.5	10	19	680
3/8	1/8	KRRB6-2	29	16	10	22	680
3/8	1/4	KRRB6-4	32	19	11	22	680
1/2	1/8	KRRB8-2	30	14	10	27	680
1/2	1/4	KRRB8-4	32	16	11	27	680
1/2	3/8	KRRB8-6	35	19	13	27	680
5/8	1/2	KRRB10-8	43	27	16	32	680
3/4	1/4	KRRB12-4	29	10	11	32	680
3/4	3/8	KRRB12-6	35	16	13	32	680
3/4	1/2	KRRB12-8	41	22	16	32	680
1	1/4	KRRB16-4	33	12	11	41	500
1	3/8	KRRB16-6	33	12	13	41	500
1	1/2	KRRB16-8	33	12	16	41	500
1	3/4	KRRB16-12	45	24	19	41	500
1-1/4	3/8	KRRB20-6	34	14	13	50	500
1-1/4	1/2	KRRB20-8	34	14	16	50	500
1-1/4	3/4	KRRB20-12	34	14	19	50	500
1-1/4	1	KRRB20-16	51	30	20	50	500
1-1/2	1/2	KRRB24-8	41	15	16	55	500
1-1/2	3/4	KRRB24-12	41	15	19	55	500
1-1/2	1	KRRB24-16	41	15	20	55	500
1-1/2	1-1/4	KRRB24-20	59	33	20	55	500
2	1	KRRB32-16	47	17	20	70	500
2	1-1/4	KRRB32-20	47	17	20	70	500
2	1-1/2	KRRB32-24	47	17	25	70	500