


### 3 Long sweep bend 90°, ISO/EN G8

EN		Dim. [inch]	Code	b [mm]	
-	B	¼	<b>770 003 102</b>	33	
-	G	¼	<b>770 003 202</b>	33	
•	B	⅜	<b>770 003 103</b>	42	
•	G	⅜	<b>770 003 203</b>	42	
•	B	½	<b>770 003 104</b>	48	
•	G	½	<b>770 003 204</b>	48	
•	B	¾	<b>770 003 105</b>	60	
•	G	¾	<b>770 003 205</b>	60	
•	B	1	<b>770 003 106</b>	75	
•	G	1	<b>770 003 206</b>	75	
•	B	1 ¼	<b>770 003 107</b>	95	
•	G	1 ¼	<b>770 003 207</b>	95	
•	B	1 ½	<b>770 003 108</b>	105	
•	G	1 ½	<b>770 003 208</b>	105	
•	B	2	<b>770 003 109</b>	130	
•	G	2	<b>770 003 209</b>	130	
-	G	2 ½	<b>770 003 210</b>	165	

### 40 Long sweep bend 45°, ISO/EN G4/45°



EN		Dim. [inch]	Code	a [mm]	b [mm]	z [mm]	
•	B	¼	<b>770 040 102</b>	26	21	16	
•	G	¼	<b>770 040 202</b>	26	21	16	
•	B	⅜	<b>770 040 103</b>	30	24	20	
•	G	⅜	<b>770 040 203</b>	30	24	20	
•	B	½	<b>770 040 104</b>	36	30	23	
•	G	½	<b>770 040 204</b>	36	30	23	
•	B	¾	<b>770 040 105</b>	43	36	28	
•	G	¾	<b>770 040 205</b>	43	36	28	
•	B	1	<b>770 040 106</b>	51	42	34	
•	G	1	<b>770 040 206</b>	51	42	34	
•	B	1 ¼	<b>770 040 107</b>	64	54	45	
•	G	1 ¼	<b>770 040 207</b>	64	54	45	
•	B	1 ½	<b>770 040 108</b>	68	58	49	
•	G	1 ½	<b>770 040 208</b>	68	58	49	
•	B	2	<b>770 040 109</b>	81	70	57	
•	G	2	<b>770 040 209</b>	81	70	57	
•	B	2 ½	<b>770 040 110</b>	99	86	72	
•	G	2 ½	<b>770 040 210</b>	99	86	72	
•	B	3	<b>770 040 111</b>	113	100	83	
•	G	3	<b>770 040 211</b>	113	100	83	
-	B	4	<b>770 040 112</b>	141	130	105	
-	G	4	<b>770 040 212</b>	141	130	105	