


## 271

### Socket, right and left hand thread, ISO/EN M2 R-L

RT ... right hand thread, LT ... left hand thread




EN		Dim. [inch]	Code	a [mm]	z1 [mm]
•	B	3/8	<b>770 271 103</b>	30	10
•	G	3/8	<b>770 271 203</b>	30	10
•	B	1/2	<b>770 271 104</b>	36	10
•	G	1/2	<b>770 271 204</b>	36	10
•	B	3/4	<b>770 271 105</b>	39	9
•	G	3/4	<b>770 271 205</b>	39	9
•	B	1	<b>770 271 106</b>	45	11
•	G	1	<b>770 271 206</b>	45	11
•	B	1 1/4	<b>770 271 107</b>	50	12
•	G	1 1/4	<b>770 271 207</b>	50	12
•	B	1 1/2	<b>770 271 108</b>	55	17
•	G	1 1/2	<b>770 271 208</b>	55	17
-	B	2	<b>770 271 109</b>	65	17
-	G	2	<b>770 271 209</b>	65	17

## 280

### Hexagon nipple, ISO/EN N8

ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations.



EN		Dim. [inch]	Code	a [mm]	s [mm]
ST.	B	1/8	<b>770 280 101</b>	29	17
ST.	G	1/8	<b>770 280 201</b>	29	17
ST.	B	1/4	<b>770 280 102</b>	36	19
ST.	G	1/4	<b>770 280 202</b>	36	19
•	B	3/8	<b>770 280 103</b>	38	22
•	G	3/8	<b>770 280 203</b>	38	22
•	B	1/2	<b>770 280 104</b>	44	28
•	G	1/2	<b>770 280 204</b>	44	28
•	B	3/4	<b>770 280 105</b>	47	33
•	G	3/4	<b>770 280 205</b>	47	33
•	B	1	<b>770 280 106</b>	53	42
•	G	1	<b>770 280 206</b>	53	42
•	B	1 1/4	<b>770 280 107</b>	57	50
•	G	1 1/4	<b>770 280 207</b>	57	50
•	B	1 1/2	<b>770 280 108</b>	59	55
•	G	1 1/2	<b>770 280 208</b>	59	55
•	B	2	<b>770 280 109</b>	68	70
•	G	2	<b>770 280 209</b>	68	70
•	B	2 1/2	<b>770 280 110</b>	75	85
•	G	2 1/2	<b>770 280 210</b>	75	85
•	B	3	<b>770 280 111</b>	83	100
•	G	3	<b>770 280 211</b>	83	100
•	B	4	<b>770 280 112</b>	95	131
•	G	4	<b>770 280 212</b>	95	131