



Comfort-Lok

Durable, modular matting

- Ideal anti-fatigue matting for greasy or oily areas.
- Hardwearing natural SBR rubber and nitrile.
- Suitable for high temperature environments.
- Comfortable standing surface for operatives.
- Diamond patterned surface provides underfoot grip.
- Conforms to Slip Resistance Test EN13552 Category R9.
- Interlocking modules or single mat (edged all round).

Product height: 12.5mm

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
0.7 x 0.8 (end piece)	5	17.5 x 17.5 x 75	Boxed	1	42	Black	CL010001
0.7 x 0.8 (middle piece)	5	17.5 x 17.5 x 75	Boxed	1	42	Black	CL010002
0.7 x 0.8 (edged all round)	5	17.5 x 17.5 x 75	Boxed	1	42	Black	CL010004

Material:	Natural Rubber/25% Nitrile blend
Surface Finish:	Diamond Plate
Product Height:	12.5mm nominal
Operating Temperature:	-30° to +50°C
Resistance to Chemicals:	Natural rubber/nitrile blend offers an increased resistance to mineral oils and aggressive machine coolants.
Environmental Resistance:	Water and Acid not fuels and degreasing oils.
UV Resistance:	N/A
Typical Applications:	All industrial environments.
Installation Method:	Loose lay
Cleaning Method:	Pressure hose.
Product Performance:	Conforms to slip resistance test EN13552 Category R9
Product Performance:	Fatigue: ● ● ● Slip Resistance: ● ● ● Wear: ● ● ● Low ‡ High ● → ● ● ● ● ●
Flame Retardancy:	Not flame retardant.
Country of Origin:	Sri Lanka
Other:	Silicone is used in the production process of the mats and a residue will possibly be left on the product.

End of document

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.