



COBAmat Standard

An excellent all-rounder

- Excellent resistance to wear and tear
- Optional extras: bevelled safety edging (factory fitted) and fixing blocks
- Interwoven PVC matting with open holes (22mm x 22mm)
- Conforms to Slip Resistance Test DIN 51097 Category B
- Fire tested to DIN 54332 (B2) part of DIN 4102

Product height: 12mm

| Dimensions (m.) | Weight Kg | Packaging Dimensions (cm.) | Packaging Type | Packaging Volume (m.) | Packaging Quantity | Colour | Part Code |
|-----------------|-----------|----------------------------|----------------|-----------------------|--------------------|--------|-----------|
| 0.6 x 5 | 15 | 60 x 25 | Roll | 1 | 20 | Black | CS010605 |
| | | | | | | Blue | CS020605 |
| | | | | | | Green | CS040605 |
| | | | | | | Red | CS030605 |
| 0.6 x 10 | 30 | 60 x 40 | Roll | 1 | 12 | Black | CS010610 |
| | | | | | | Blue | CS020610 |
| | | | | | | Green | CS040610 |
| | | | | | | Red | CS030610 |
| 0.9 x 5 | 23 | 90 x 25 | Roll | 1 | 12 | Black | CS010905 |
| | | | | | | Blue | CS020905 |
| | | | | | | Green | CS040905 |
| | | | | | | Red | CS030905 |
| 0.9 x 10 | 45 | 90 x 40 | Roll | 1 | 9 | Black | CS010910 |
| | | | | | | Blue | CS020910 |
| | | | | | | Green | CS040905 |
| | | | | | | Red | CS030910 |
| 1.2 x 5 | 30 | 120 x 25 | Roll | 1 | 12 | Black | CS011005 |
| | | | | | | Blue | CS021005 |
| | | | | | | Green | CS041205 |
| | | | | | | Red | CS031205 |
| 1.2 x 10 | 60 | 120 x 40 | Roll | 1 | 9 | Black | CS011210 |
| | | | | | | Blue | CS021210 |
| | | | | | | Green | CS041210 |
| | | | | | | Red | CS031210 |

Continued on next page

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.

Material: PVC extrusions.
Surface Finish: Cross ribbed lattice effect
Product Height: 12mm nominal
Hole Size: 22mm x 22mm
Operating Temperature: -20° C - +60°C
Resistance to Chemicals: PVC is resistant to many different chemicals, alkalis and general industrial chemicals. Please contact the sales office for more specific details.

Environmental Resistance: Suitable for wet and dry areas.
UV Resistance: Resistant to UV, but please note that red is not colourfast in direct sunlight.

Typical Applications: Ideal for all industrial environments, especially machine tool areas where swarf is in abundance.
Conforms to BIA anti-slip test.

Installation Method: Loose lay/reversible
Accessories: Factory fitted edging where required.
Fixing cubes to secure mat to the floor.
Cleaning Method: Pressure hose with mild detergent.
Product Performance: Conforms to the BIA anti slip test and slip resistance test EN 13552 Category R10

Product Performance: Fatigue: ● ● ● ●
Slip Resistance: ● ● ● ●
Wear: ● ● ● ●
Low ‡ High ● → ● ● ● ● ●

Flame Retardancy: Fire tested to DIN 54332(B2) Part of DIN 4102
Country of Origin: UK

End of document

The information contained within this datasheet is for guidance only. The data and suggested application are not exhaustive. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed into some applications.