

Airless Spray Gun

Model No.: AP313



811

- In-handle paint filter reduces tip clogs and improves finish.
- Well-balanced and lightweight.
- Full Trigger(4-Finger) locks open for flushing and cleaning.
- Ergonomic design and easy trigger pivot reduce operator fatigue.

This high pressure spray gun using the principle of the independent design of flow channel, and the feed tube is adopts stainless steel material, make the spray gun pressurized strength stronger and security.



SPECIFICATIONS

Model No. 811	Type of Feed: Pressure
Max. standard Nozzle: $\Phi 0.019"$ (517)	Operating Pressure: 5000PSI
Pattern Width: 254-305mm	Paint Inlet Connection: 1/4-18-NPSM
Paint Capacity: 300mm	

818C

- In-handle paint filter reduces tip clogs and improves finish.
- Well-balanced and lightweight.
- Full Trigger(4-Finger) locks open for flushing and cleaning.
- Ergonomic design and easy trigger pivot reduce operator fatigue.

SPECIFICATIONS

Model No. 818C	Type of Feed: Pressure
Max. standard Nozzle: $\Phi 0.017"$ (517)	Operating Pressure: 3600PSI
Pattern Width: 254-305mm	Paint Inlet Connection: 1/4-18-NPSM
Paint Capacity: 300mm	



Four finger trigger



Two finger trigger

AIRLESS PAINT SPRAYER ACCESSORIES SWITCH TIPS (Inter changeable for Titan graco sprayer)



AP8605
(RP860.5)

For 818c
four finger trigger.

		Orifice Size-Inches																								
		IN	(MM)	.007	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	.039	.043	.045	.051	.055	.063	.065	
Fan Width	2.4 (51-102)			207	109	111	113	115	217	219	211	223	225					235								
	4.6 (102-152)			307	309	311	*313	*315	317	319	321	323	325	327				331								
	6-8 (152-203)				409	411	*413	*415	417	419	421	423	425	427	429			433	435	439	443					
	8-10 (203-254)				509	511	*513	*515	*517	*519	*521	*523	525	527	529	531	533	535					451	455		
	10-12 (254-305)				609	611	613	615	617	*619	*621	623	625	627	629	631	633	635				645	651	655	665	
	12-14 (305-356)																									
	14-16 (356-406)																									
	16-18 (406-457)																									
	18-20 (457-508)																									
	FLOW (gpm)				.05	.09	.12	.18	.24	.31	.38	.47	.57	.67	.77	.90	1.03	1.17	1.31	1.31	1.63	1.95	2.17	2.79	3.25	4.26
FLOW (gpm)				.20	.33	.49	.69	.91	1.17	1.47	1.79	2.15	2.54	2.96	3.42	3.90	4.42	4.98	6.18	7.51	8.23	10.57	12.29	16.13	17.17	

* Is Optional Tips Example: for a tip with a 0.013 in. (0.33mm) orifice and a 6 in. (152mm) pattern, order 313.



AP8604
(RP860.4)

For 818c
two finger trigger.

		Orifice Size-Inches																
		IN	(MM)	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	
Fan Width	2.4 (51-102)																	
	4.6 (102-152)			209	*211	213	215	217	219									
	6-8 (152-203)			309	311	313	*315	317	319	321	423							
	8-10 (203-254)				*411	*413	*415	417	419	421								
	10-12 (254-305)				511	513	*515	*517	*519	521	*523	525	527					
	12-14 (305-356)						615	617	*619	*621	*623	625	627	*629	631		635	
	14-16 (356-406)																635	
	FLOW (gpm)				.09	.12	.18	.24	.31	.38	.47	.57	.67	.77	.90	1.03	1.17	1.31
	FLOW (gpm)				.33	.49	.69	.91	1.17	1.47	1.79	2.15	2.54	2.96	3.42	3.90	4.42	4.96

* Is Optional Tips Example: for a tip with a 0.013 in. (0.33mm) orifice and a 8 in. (203mm) pattern, order 413.



AP8606
(RP860.12)

For 811

		Orifice Size-Inches															
		IN	(MM)	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	.039	.055
Fan Width	2 (51)			213	215	217	219										
	4 (102)				315	317	319	321	323	325	327	329	331	333	335		355
	4-8 (102-204)					417	419	421	423	425	427	429	431		435		
	8-12 (204-305)							621	623	625	627	629	631		635	639	
	FLOW (gpm)			.18	.24	.31	.38	.47	.57	.67	.77	.90	1.03	1.17	1.31	1.63	3.25
FLOW (gpm)			.69	.91	1.17	1.47	1.79	2.15	2.54	2.96	3.42	3.90	4.42	4.96	6.18	12.29	

* Is Optional Tips Example: for a tip with a 0.015 in. (0.38mm) orifice and a 4 in. (102mm) pattern, order 315.

Oneseals
RP8605-1



AIRLESS PAINT SPRAYER ACCESSORIES

Tip Guard

- Tip Guard with 7/8", thread size.
- Titan graco sprayer.



AP8647-1
• Stainless steel



AP8642
• 270° rotation tip guard.


Filter

- Inlet filter for easy and quick cleaning, only available for AP8618, 488 and R45.

AP8654
(819-08)
• Fit for AP8618



AP8652
(490.2-04)
• Fit for 488



AP8653
(R45.2.1)
• Fit for R45



- Various of inlet screen filter fit for AP8620, AP8622, AP8623, AP8624 819, 470, 488.

Filter



AP8644
(RP816.6)
• Filter for airless sprayer
60 mesh, 100 mesh available.



AP8645-1
(RP860.3)
• 50 mesh, 100mesh, 150mesh available.
• Titan graco sprayer.



AP8656-2
• Fit for AP8619,
AP8618.



AP8656
(AP860.1B 7/8")
• Fit for 470,
488, 520.



AP8656-4
• Fit for AP8620, AP8622,
AP8623, AP8624.



AP8656-1
(AP860.1A 3/4")



AP8656-3
(R45.8.1)
• Fit for R45.