


Quick Release Pneumatic Hose Couplings



QAC Claw Couplings

QAC 1 Hose Tail, Forged Steel

- Extremely robust, durable coupling of forged steel, hardened, zinc plated and yellow passivated (free of chrome VI), equivalent to type Atlas Copco
- With oil-resistant rubber ring GOER, on request with steam-resistant rubber ring GDOR (up to 200°C) against extra charge
- Maximum bore for maximum flow capacity to reach full tool performance
- Turned gasket seat, therefore 100% tight
- Turned stem profile for perfect fit of the hose
- High quality coupling for compressed air in construction and industry



PART NO	HOSE I.D	DN	TEMP.	MATERIAL	SEAL	THREADS	MEDIUM	CLAW DISTANCE
QAC138	3/8"	8	-40°C-+95°C	steel hardenend	NBR	ISO 228	Compressed Air	42 mm
QAC112	1/2"	10.5	-40°C-+95°C	steel hardenend	NBR	ISO 228	Compressed Air	43 mm
QAC134	3/4"	17	-40°C-+95°C	steel hardenend	NBR	ISO 228	Compressed Air	44 mm
QAC112	1"	20	-40°C-+95°C	steel hardenend	NBR	ISO 228	Compressed Air	45 mm