

CP870 Dual Action Sander



Features:

- PSA sanding pad
- Insulated grip & lock off throttle to prevent accidental start ups
- Power regulator for precise control

Benefits:

- Operator comfort
- Excellent for blending & smoothing filler, feather edging & pre-paint preparation



Part number	T023990	
Model	CP870	
Pad diameter	150 mm	6"
Pad type Hook & Loop	no	
Pad type PSA	yes	
Paper size	150 mm	6"
Orbit diameter	3/8 mm	10"
Free speed	10000 rpm	
Pad holes number	0	
Spindle thread	5/16-24	
Weight	1.93 kg	4.25 lb
Noise level	83 db(A)	
Sound Power	94 db(A)	
Vibration (ISO-8662-8)	6.2 m/s ²	
Vibration a (ISO-28927-3)	13.6 m/s ²	
Vibration K (ISO-28927-3)	4.3 m/s ²	
Average air consumption	3.8 l/s	8 cfm
Average air consumption	227 l/mn	8 cfm
Actual air consumption	7.6 l/s	18 cfm
Actual air consumption	453 l/mn	18 cfm
Free speed air consumption	8.5 l/s	18 cfm
Min. hose size	10 mm	3/8"
Air inlet thread size	1/4 NPTF in.	