

Stainless Steel

Nominal Diameter

7,4 = 42 mm²



Rectus Series

25

Low Pressure



Technical Description

Universal industrial coupling with standard European profile for use with gaseous, liquid and aggressive media.

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use. The collar design minimises damage to the valve body.

Dust Protections (P. 319)
for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*
-15°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.



Working Pressure**

35 bar
** maximum static working pressure with safety factor 4 to 1.

35 bar

8 bar

Features

- Minimal, almost imperceptible leakage when uncoupling
- No air locked into the system during the coupling process

Material

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Interchangeability

- Rectus 26
- Cejn 320
- various German Products

Flow diagrams

