

Trigger Gun with Electronic In-line Flow Meter

Manual Trigger Nozzle for use with Diesel gasoline, B100 biodiesel and oils to SAE 90.

Features:

Material: Aluminium

Seal: Viton and fluorinated silicone rubber

Inlet: 1"

Outlet: 15/16"

Weight: 1.3Kgs

Max Pressure: 0.18MPa

Flow rate: 10~60L/Min

Accuracy: +/-0.8% (adjustable)

Instructions For CD-OG01

1) Reset to "zero"

Press "DISPLAY" for 1 second reset to zero.

2) Cumulative Total

Press "CALIBRATE" indicating the cumulative total fuelling.

When the cumulative total reach a max reading 999,999. It will automatically reset to Zero.

3) Calibrate adjusting

Press "CALIBRATE" and hold for 3 seconds, press "DISPLAY" or "CALIBRATE" for adjusting. For example, when the meter show 103L while the liquid comes 100L, put the figure $103/100=1.0300$. And the computer display is programmed to turn back to stand-by situation after 5 seconds.

4) Unit switch

Press "CALIBRATE" and hold for 3 seconds, press" DISPLAY" for 5 seconds and then press" CALIBRATE" for units with among Litres(L) / Gallons (GAL) / Pints(PT) / Quarts(QT). And the computer display is programmed to turn back to stand-by situation after 5 seconds.

5) For the most accurate reason, before using make sure there is no air in the system and meet the meter's minimum flow rate requirements

