
# ART.EH1106

C.P forged mini ball valve red handle; FxM ISO228 thread EH1106: red handle EH1108: black handle

Size:1/8"~3/4"



# C

# Technical features:

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems. Minimum and maximum working temperature:

-10°C, 110°C.

Available: in all sizes from 1/8" up to 3/4".

# Materials:

Valve Body: C.P. Polished Brass

Handle: ABS

Ball: Hard chrome-plated brass

Seal: P.T.F.E. Stem: Brass Stem-seal: Brass O-Ring: NBR


| Size(mm) | 1/8" | 1/4" | 3/8" | 1/2" | 3/4" |
|----------|------|------|------|------|------|
| Α        | 36   | 39.5 | 40   | 46   | 54   |
| В        | 5.5  | 8    | 8    | 9.5  | 13.5 |
| С        | 22   | 22   | 22   | 22   | 22   |
| D        | 19   | 21   | 21   | 25   | 30   |
| Е        | 26.5 | 28   | 28   | 29.5 | 32.5 |

# **ART.EH1107**

C.P forged mini ball valve red handle; FxF ISO228 thread EH1107: red handle EH1109: black handle

Size:1/8"~3/4"





# Technical features:

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Minimum and maximum working temperature:

-10°C, 110°C.

Available: in all sizes from 1/8" up to 3/4".

# Materials:

Valve Body: C.P. Polished Brass

Handle: ABS

Ball: Hard chrome-plated brass


Seal: P.T.F.E. Stem: Brass Stem-seal: Brass O-Ring: NBR

| Size(mm) | 1/8" | 1/4" | 3/8" | 1/2" | 3/4" |
|----------|------|------|------|------|------|
| А        | 36   | 39.5 | 40   | 46   | 54   |
| В        | 5.5  | 8    | 8    | 9.5  | 13.5 |
| С        | 22   | 22   | 22   | 22   | 22   |
| D        | 19   | 21   | 21   | 25   | 30   |
| Е        | 26.5 | 28   | 28   | 29.5 | 32.5 |

# **ART.EH1108**

C.P forged mini ball valve red handle; FxM ISO228 thread EH1106: red handle EH1108: black handle

Size:1/8"~3/4"



# C A A A

# Technical features:

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Minimum and maximum working temperature:

-10°C, 110°C.

Available: in all sizes from 1/8" up to 3/4".

# Materials:

Valve Body: C.P. Polished Brass

Handle: ABS

Ball: Hard chrome-plated brass

Seal: P.T.F.E. Stem: Brass Stem-seal: Brass O-Ring: NBR


| Size(mm) | 1/8" | 1/4" | 3/8" | 1/2" | 3/4" |
|----------|------|------|------|------|------|
| А        | 36   | 39.5 | 40   | 46   | 54   |
| В        | 5.5  | 8    | 8    | 9.5  | 13.5 |
| С        | 22   | 22   | 22   | 22   | 22   |
| D        | 19   | 21   | 21   | 25   | 30   |
| E        | 26.5 | 28   | 28   | 29.5 | 32.5 |

# **ART.EH1109**

C.P forged mini ball valve red handle; FxF ISO228 thread EH1107: red handle EH1109: black handle

Size:1/8"~3/4"





# Technical features:

Suitable for domestic water services, heating and air-conditioning plants, compressed air systems.

Minimum and maximum working temperature:

-10°C, 110°C.

Available: in all sizes from 1/8" up to 3/4".

# Materials:

Valve Body: C.P. Polished Brass

Handle: ABS

Ball: Hard chrome-plated brass

Seal: P.T.F.E. Stem: Brass Stem-seal: Brass O-Ring: NBR

| Size(mm) | 1/8" | 1/4" | 3/8" | 1/2" | 3/4" |
|----------|------|------|------|------|------|
| A        | 36   | 39.5 | 40   | 46   | 54   |
| В        | 5.5  | 8    | 8    | 9.5  | 13.5 |
| С        | 22   | 22   | 22   | 22   | 22   |
| D        | 19   | 21   | 21   | 25   | 30   |
| E        | 26.5 | 28   | 28   | 29.5 | 32.5 |